

TECHNICAL SPECIFICATIONS (METRIC)

Region spec	Service pressure	Oxygen capacity	Diameter	Length	Weight	Internal volume	Thread size	Part number
	<i>bar</i>	<i>l</i>	<i>mm</i>	<i>mm</i>	<i>kg</i>	<i>l</i>		
USA	207	181.2	83.8	251.5	0.7	0.8	0.750-16 UNF	M06D
USA	207	243.5	83.8	309.9	0.8	1.1	0.750-16 UNF	M09B
USA	207	436	101.6	373.4	1.31	2	0.750-16 UNF	M15A
USA	207	611.6	114.3	393.7	1.49	2.8	0.750-16 UNF-2B	M22A
USA	207	682.4	114.3	441	2	3.1	0.750-16 UNF-2B	M24A
USA	207	1868.9	172.7	525.8	4.2	8.5	0.750-16 UNF-2B	M66A
-	-	-	-	-	-	-	-	-
Europe	300	306	85	294	0.8	1	M18 × 1.5 CLASS 6H	M10C
Europe	207	242	101	233	0.9	1.1	0.625-18UNF-2B	M09A
Europe	300	612	101	386	1.5	2	M18 × 1.5 CLASS 6H	L19C
Europe	300	917	114	443	1.9	3	M18 × 1.5 CLASS 6H	L29C

INFO

Specifications subject to change.

 TECHNICAL SPECIFICATIONS (IMPERIAL)

 INFO